

Mirror (PMFM Series)


The Polarization Maintaining Faraday Mirror is a passive device that provides 90 degree rotation regarding to the polarization state of the input light. The PMFM offers excellent performance including the lowest possible insertion loss and enviromental stability. It is used in amplifiers, fiber lasers and fiber instruments to minimize the polarization effect.

Specifications

Parameter	Unit	Value
Center Wavelength (λ_c)	nm	1310, 1480 or 1550
Operating Wavelength Range	nm	$\lambda_c \pm 15$
Typ. Insertion Loss	dB	0.4
Max. Insertion Loss	dB	0.6
Faraday Rotation Angle (single pass)	degree	45
Max. Rotation Angle Tolerance, λ_c , 23 °C	degree	± 1
Min. Extinction Ratio	dB	20
Fiber Type		PM Panda fiber or specify
Max. Optical Power (Continuous Wave)	mW	300
Max. Tensile Load	N	5
Operating Temperature	°C	-5 to +70
Storage Temperature	°C	-40 to +85

*IL is 0.3 dB higher, RL is 5 dB lower, and ER is 2 dB lower for each connector added. Connector key is aligned to slow axis

Package Dimensions



Ordering Information

PMFM-①②③④

①①: Wavelength	②: Connector Type	③: Fiber Type	④: Fiber Length
31 - 1310 nm	1 - FC/UPC	B - 250 μm Panda fiber	Q - 0.75 m
48 - 1480 nm	2 - FC/APC	D - 400 μm Panda fiber	S - Specify
55 - 1550 nm	3 - SC/UPC	L - 900 μm loose tube	
SS - Specify	4 - SC/APC	S - Specify	
	N - None		

